



COMPRESSOR SPECIFICATIONS

BORE	Ø29.3 mm
STROKE	32.8 mm
DISPLACEMENT PER REVOLUTION	154.9 cc/rev
NUMBER OF CYLINDERS	7
MAXIMUM ALLOWABLE r.p.m.	7000 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000 r.p.m.
REFRIGERANT	HFC134a
OIL(SP-10 OR EQUIV.)	135 cc
ROTATION(CLUTCH SIDE VIEW)	CLOCKWISE
WEIGHT	kg

CLUTCH SPECIFICATIONS

RATED VOLTAGE	DC 24 V
BREAKAWAY TORQUE	3.5 kg-m
MINIMUM ENGAGEMENT VOLTAGE	16V max
POWER CONSUMPTION	42 W (Cu)
MAXIMUM ALLOWABLE r.p.m.	7000 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000 r.p.m.
BELT TYPE	A
PULLEY DIAMETER	Ø132 mm
WEIGHT	kg



MATERIAL	PART NO. 8264	NAME COMPRESSOR
THIRD ANGLE PROJECTION	SCALE 1:1	MODEL SD7H15KG8264
DESIGN BY	CHECKED BY	APPROVED BY
REVISION RECORD	BY	DATE
		DRAWING NO. 8264-6000S